



ARMOUR MULTI-USE PROTECTION TAPE



ARMOUR SPILL
PROTECTION



CLEAN REMOVAL

Armour Multi-Use Protection Tape is a versatile temporary protection solution for hard surfaces, providing clean removal while preventing scuffs, scratches, dust, and other minor jobsite damage.

- Made from thick, durable film for reliable surface protection
- Protects a wide range of hard surfaces without leaving residue
- Cost-effective and easy to apply, offering quick coverage for multiple applications
- Removes cleanly from interior surfaces for up to 180 days for minimal disruption
- Commonly used to protect showers, bathtubs, sinks, handrails, door and window frames, curtainwall glazing, mullions, door thresholds, and more from minor construction damage like scuffs, scratches, or dust in low-traffic or short-term projects

ITEM CODE	SIZE	WEIGHT	PACKAGED
AMPT3100	3in X 100ft (25 sq.ft.)	0.7lb	48 / box
AMPT6100	6in X 100ft (50 sq.ft.)	1.4lb	24 / box
AMPT12100	12in x 100ft (100 sq.ft.)	2.8lb	12 / box

ARMOUR MULTI-USE PROTECTION TAPE

<u>Physical Properties</u>	<u>Details</u>
Product Material	Polyethylene (PE) Film
Adhesive Type	Water Based Acrylic 180 Day UVR
Product Colour	Blue
Logo Colour	White
Shelf Life	12 months
Clean Removal* / UV Rating	6 months
Packaging Size	Varies depending on size
HS Code	3919.10.99.90

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Application Temperature Range	-15 35°C ±10%	5 95°F ±10%
Operating Temperature Range	-10 35°C ±10%	14 95°F ±10%
Product Thickness	0.127 mm	5 mil
Adhesive Thickness	0.007 mm	0.27 mil
TOTAL Product Thickness	0.134 mm	5.27 mil
Product Width	Varies	Varies
Product Height/Length	30.5 m	100 ft
Tensile Strength	2.657 Kgf/25mm	5.85 lbs/in
Adhesion Strength	0.2 Kgf/25mm	0.44 lbs/in
Unwinding Force	0.05 Kgf/25mm	0.11 lbs/in
Elongation at Break		>300 %

*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.