

ARMOUR PREMIUM COUNTERTOP FILM



ARMOUR SPILL
PROTECTION



CLEAN REMOVAL

Armour Premium Countertop Film can be safely applied to the surface without damaging the countertop or leaving residue. With 45 day clean removal*, this works as a great solution for protecting granite, marble, quartz, and various other countertop surfaces from scuffs, scratches, paint, and more.

ITEM CODE	SIZE	WEIGHT	PACKAGED
APCTF24600	24in X 600ft (1200 sq.ft.)	20lb	42 / skid
APCTF30600	30in X 600ft (1500 sq.ft.)	25lb	42 / skid

ARMOUR PREMIUM COUNTERTOP FILM

<u>Physical Properties</u>	<u>Details</u>
Product Material	Polyethylene (PE) Film
Adhesive Type	Water Based Acrylic Solvent
Product Colour	Translucent
Shelf Life	12 months
Clean Removal* / UV Rating	1.5 months
Packaging Size	1 roll per carton
HS Code	3919.90.00.20

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Application Temperature Range	-15 35°C ±10%	5 95°F ±10%
Operating Temperature Range	-10 35°C ±10%	14 95°F ±10%
Product Thickness	0.076 mm	3 mil
Adhesive Thickness	0.01 mm	0.39 mil
TOTAL Product Thickness	0.086 mm	3.39 mil
Product Width	Varies	Varies
Product Height/Length	183 m	600 ft
Tensile Strength	2.657 kgf/25mm	5.85 lbs/in
Adhesion Strength	0.2 kgf/25mm	0.44 lbs/in
Unwinding Force	0.03 kgf/25mm	0.07 lbs/in
Elongation at Break		> 300 %

*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.