



# ARMOUR TAPE



ARMOUR SPILL  
PROTECTION



CLEAN REMOVAL

Armour Tape is a versatile jobsite tape solution designed for seaming and fastening temporary surface protection products while offering clean removal and reliable performance across a wide range of construction projects.

- Polyethylene-backed and UV-stabilized for durability in demanding environments
- Provides strong adhesion to hold protection materials securely in place
- Clean removal makes it a dependable alternative to duct tape and other site tapes
- Serrated edges on every roll allow for quick and easy tearing, saving time on projects
- Commonly used for seaming materials to each other or to finished surfaces with clean removal of up to 60 days in minor to major construction projects

ITEM CODE	SIZE	WEIGHT	PACKAGED
AT2180	2in X 180ft	0.6lb	24 / box
AT3180	3in X 180ft	1.4lb	16 / box

# ARMOUR TAPE

<u>Physical Properties</u>	<u>Details</u>
<b>Product Material</b>	Low Density Polyethylene (LDPE) Film
<b>Adhesive Type</b>	UV Stabilized Synthetic Rubber
<b>Product Colour</b>	Red, White, Black
<b>Shelf Life</b>	12 months
<b>Clean Removal* / UV Rating</b>	60 Days
<b>Packaging Size</b>	2 in 24 rolls per case 3 in 16 rolls per case

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
<b>Application Temperature Range</b>	+7 49°C ±10%	45 120°F ±10%
<b>Operating Temperature Range</b>	-7 93°C ±10%	20 200°F ±10%
<b>Product Thickness</b>	0.18 mm	7 mil
<b>TOTAL Product Thickness</b>	0.18 mm	7 mil
<b>Product Width</b>	Varies	Varies
<b>Product Height/Length</b>	Varies	Varies
<b>Tensile Strength</b>	9.38 Kgf/25mm	20.64 lbs/in
<b>Adhesion Strength</b>	2.09 Kgf/25mm	4.6 lbs/in
<b>Unwinding Force</b>	0.05 Kgf/25mm	0.11 lbs/in
<b>Elongation at Break</b>		75 %

\*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.