

ARMOUR DOOR-GUARD



FOAM BACKED


 RECYCLED
CONTENT

 ARMOUR SPILL
PROTECTION


RE-USABLE

The Armour Door-Guard is probably the fastest and easiest way to protect a door from potential impact and jobsite damage.

- 4mm thick fluted plastic sheet for great durability and impact resistance.
- Soft foam backing prevents scuffs and scratches on new doors.
- Easy to install: simply hang the Door-Guard on top of the door and unfold it on either side, then use the attached Velcro straps to hold it in place.
- Comes pre-folded, requiring little space for easy storage.
- Highly reusable from project to project for both cost-effectiveness and sustainability.
- Most commonly used to protect high-value doors where you can't afford damage to occur.

ITEM CODE	SIZE	WEIGHT	PACKAGED
ADGD3583	35in X 83in (fits 36in X 7ft door)	5.8lb	5 / pack 100 / skid
ADGD3595	35in X 95in (fits 36in X 8ft door)	6lb	5 / pack 100 / skid
ADGD3783	37in X 83in (fits 38in X 7ft door)	5.8lb	5 / pack 100 / skid
ADGD3795	37in X 95in (fits 38in X 8ft door)	6.6lb	5 / pack 100 / skid

ARMOUR DOOR-GUARD

<u>Physical Properties</u>	<u>Details</u>
Product Material	Polypropylene (PP) Fluted/Foam
Product Colour	Blue/White
Logo Colour	White
Packaging Size	5 pieces per pack
HS Code	3921.19.00.90
Notes / Comments	36" & 38" Wide and 84" & 96" Tall options available

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Operating Temperature Range	-20 40°C ±10%	-4 104°F ±10%
Product Thickness	4 mm	157 mil
TOTAL Product Thickness	4 mm	157 mil
Product Weight / Density	650 g/sq.m	0.13 lbs/sq.ft.
TOTAL Product Weight / Density	650 g/sq.m	0.13 lbs/sq.ft.
Product Width	890 mm / 965 mm	36 in / 38 in
Product Height/Length	2108 mm	83 in
Crush Test Rating	439 Kgf/sq.m	90 lbs/sq.ft.