

# ARMOUR SECURE-SEAM TAPE



ARMOUR SPILL  
PROTECTION

Armour Secure-Seam Tape is a cost-effective seaming solution designed to hold temporary surface protection materials securely in place, ensuring a fully sealed off solution on jobsites.

- Constructed with durable adhesive backing for strong hold on protection materials
- Designed for seaming surface protection products to themselves, not to finished surfaces – for a tape solution that offers clean removal, try Armour Tape or Armour Pro-Clean Tape
- Provides dependable adhesion that prevents shifting, keeping protection secure throughout the project
- Cost-effective solution that delivers reliable performance for a range of jobsite needs
- Commonly used for seaming protection materials to each other on minor to major construction projects

ITEM CODE	SIZE	WEIGHT	PACKAGED
ASST2216	2in X 216ft	0.4lb	72 / case

# ARMOUR SECURE-SEAM TAPE

<u>Physical Properties</u>	<u>Details</u>
Product Material	Low Density Polyethylene (LDPE) Film
Adhesive Type	UV Stabilized Synthetic Rubber
Product Colour	Black
Logo Colour	White
Shelf Life	12 months
Packaging Size	72 rolls per case

<u>Specification Properties</u>	<u>Metric</u>	<u>Standard/Imperial</u>
Application Temperature Range	12 to 43°C	54 to 110°F
Operating Temperature Range	-2 to 60°C	30 to 140°F
Product Thickness	0.062 mm	2.44 mil
TOTAL Product Thickness	0.062 mm	2.44 mil
Product Width	5.08 cm	2in
Product Height/Length	65.84 m	216ft
Tensile Strength	630 N/100 mm	36lbs/in
Adhesion Strength	61 N/100 mm	57oz/in
Elongation at Break		200 %

\*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.