

ARMOUR PREMIUM HARD SURFACE FILM



GREAT FOR STAIRS



ARMOUR SPILL
PROTECTION



CLEAN REMOVAL

Armour Premium Hard Surface Film effectively protects hard surfaces from damage such as scuffs, scratches, dust, paint, drywall mud, and more. It's made from a blue tear resistant film and protects up to 45 days with clean removal*. It is fully waterproof and commonly used to protect hard floors, cabinets, lockers, and any other hard surfaces efficiently.

| ITEM CODE | SIZE | WEIGHT | PACKAGED |
|------------|----------------------------|--------|-----------|
| APHSF24500 | 24in X 500ft (1000 sq.ft) | 13lb | 42 / skid |
| APHSF36500 | 36in X 500ft (1500 sq.ft.) | 19.5lb | 42 / skid |
| APHSF48500 | 48in X 500ft (2000 sq.ft.) | 26lb | 42 / skid |

ARMOUR PREMIUM HARD SURFACE FILM

| <u>Physical Properties</u> | <u>Details</u> |
|----------------------------|-----------------------------|
| Product Material | Polyethylene (PE) Film |
| Adhesive Type | Water Based Acrylic Solvent |
| Product Colour | Blue |
| Logo Colour | White |
| Shelf Life | 12 months |
| Clean Removal* / UV Rating | 1.5 months |
| Packaging Size | 1 roll per carton |
| HS Code | 3919.90.00.20 |

| <u>Specification Properties</u> | <u>Metric</u> | <u>Standard/Imperial</u> |
|---------------------------------|----------------|--------------------------|
| Application Temperature Range | -15 35°C ±10% | 5 95°F ±10% |
| Operating Temperature Range | -10 35°C ±10% | 14 95°F ±10% |
| Product Thickness | 0.071 mm | 2.8 mil |
| Adhesive Thickness | 0.007 mm | 0.27 mil |
| TOTAL Product Thickness | 0.078 mm | 3.07 mil |
| Product Width | Varies | Varies |
| Product Height/Length | Varies | Varies |
| Tensile Strength | 2.657 kgf/25mm | 5.85 lbs/in |
| Adhesion Strength | 0.6 kgf/25mm | 1.32 lbs/in |
| Unwinding Force | 0.05 kgf/25mm | 0.11 lbs/in |
| Elongation at Break | | > 300 % |

*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.