

# ARMOUR PRO-TACK FELT



RE-USABLE



RECYCLED  
CONTENT



ARMOUR SPILL  
PROTECTION



LAYS OUT FLAT  
AND FAST



CLEAN REMOVAL



SLIP RESISTANT

Armour Pro-Tack Felt is a super strong, self-adhesive non-woven material that offers effective temporary protection on many surfaces such as walls, floors, stairs, elevators, cabinets, glass, and more. The bottom layer brings complete spill protection from liquids combined with the absorbent top layer for soaking in any moisture. It can be applied on both vertical and horizontal surfaces due to its unique self adhesive properties which offers clean removal\* on interior surfaces for up to 90 days.

| ITEM CODE | SIZE                  | WEIGHT | PACKAGED  |
|-----------|-----------------------|--------|-----------|
| APTF125   | 1m X 25m (269 sq.ft.) | 18.4lb | 12 / skid |

# ARMOUR PRO-TACK FELT

| <u>Physical Properties</u> | <u>Details</u>                          |
|----------------------------|---|
| Product Material           | 100% Polypropylene (PP) Non-woven Fiber |
| Adhesive Type              | Water Based Acrylic Solvent             |
| Product Colour             | Grey                                    |
| Shelf Life                 | 12 months                               |
| Clean Removal* / UV Rating | 3 months                                |
| Packaging Size             | 1 roll per carton                       |
| HS Code                    | 5705.00.00.00                           |

| <u>Specification Properties</u> | <u>Metric</u> | <u>Standard/Imperial</u> |
|---------------------------------|---------------|--------------------------|
| Operating Temperature Range     | 10 40°C ±10%  | 50 104°F ±10%            |
| Product Thickness               | 2.4 mm        | 95 mil                   |
| TOTAL Product Thickness         | 2.4 mm        | 95 mil                   |
| Product Weight / Density        | 350 g/sq.m    | 0.07 lbs/sq.ft.          |
| TOTAL Product Weight / Density  | 350 g/sq.m    | 0.07 lbs/sq.ft.          |
| Product Width                   | 1 m           | 39 in                    |
| Product Height/Length           | 25 m          | 82 ft                    |
| Tensile Strength                | 61 kgf/50mm   | 67.5 lbs/in              |
| Adhesion Strength               | 2 kgf/25mm    | 4.5 lbs/in               |
| Elongation at Break             | 2.5 Kn        |                          |
| Puncture Resistance             | >2.5 Kn       |                          |
| Water Absorption                |               | 400%                     |
| Oil Absorption                  |               | 470%                     |

\*Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.