

ARMOUR TAPE







ARMOUR SPILL PROTECTION



Armour Tape is polyethylene backed and UV stabilized making it excellent for use with temporary surface protection products, both to seam them together and fasten them in place. With 60 day clean removal*, Armour Tape is a great alternative to duct tape and other types, and works great as a general site tape. It comes standard with serrated edges on every roll for easy tearing, to help you save time on your project. Other colours available for special order.

ITEM CODE	SIZE	WEIGHT	PACKAGED
AT2180	2in X 180ft	0.6lb	24 / box
AT3180	3in X 180ft	1.4lb	16 / box





ARMOUR TAPE

Physical Properties	<u>Details</u>	
Product Material	Low Density Polyethylene (LDPE) Film	
Adhesive Type	UV Stabilized Synthetic Rubber	
Product Colour	Red, White, Black	
Shelf Life	12 months	
Clean Removal* / UV Rating	60 Days	
Packaging Size	2 in 24 rolls per case 3 in 16 rolls per case	

<u>Specification Properties</u>	<u>Metric</u>	Standard/Imperial
Application Temperature Range	+7 49°C ±10%	45 120°F ±10%
Operating Temperature Range	-7 93°C ±10%	20 200°F ±10%
Product Thickness	0.18 mm	7 mil
TOTAL Product Thickness	0.18 mm	7 mil
Product Width	Varies	Varies
Product Height/Length	Varies	Varies
Tensile Strength	9.38 kgf/25mm	20.64 lbs/in
Adhesion Strength	2.09 kgf/25mm	4.6 lbs/in
Unwinding Force	0.05 kgf/25mm	0.11 lbs/in
Elongation at Break		75 %

^{*}Certain additives in the product adhesive and/or material finishes of the surface it is applied to may soften the products adhesive over time, potentially leaving adhesive residue. There is no guarantee that adhesive products will not remove existing finishes when removed, due to the quality of bond on existing paint, wax, or other coatings that the adhesive product is applied to. Given the diversity of factors that can affect the use and performance of any Product, you, as the user, are solely responsible for evaluating the Product and determining whether it is fit for the intended purpose and suitable for your method of application.

